ProLite E383S-B | 15"

The revamped ProLite E383S now features a new panel generation and faster response time. Ideal as an entry-level or backup display, it scores with an impressive 1024 x 768 pixel resolution, sharp contrast of 400:1 and powerful brightness of 250 cd/m². This 15" LCD is the perfect choice for all home and office applications. Strong on picture quality and packed with ergonomic design features, the ProLite E383S gives you just what you would expect from iiyama: excellent value for money.

Technical data	
Panel	TN Wide Angle
Diagonal	15.0" (38cm)
Display area h x w	304 x 228 mm
Response time	16 msec
Contrast ratio	400 : 1 typical
Brightness	250 cd / m² typical
Viewing zone	horizontal/vertical: 120°/100°; right/left 60°/60°, up/down: 40°/60°
Display colour	16.22 Million
Pixel pitch h x v	0.297 x 0.297 mm
Horizontal sync	24 - 60 KHz
Vertical sync	55 - 75 Hz
Bandwidth	80 MHz
Native resolution	0.8 MegaPixel (1024 x 768)
Input connector	D-Sub mini 15 pin
Speaker	2 x 1,5 W (Stereo)
Included accessories	Power cable, D-Sub cable, audio cable, user manual
Optional accessories	Screen protection sheet
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers
Controls	On-Screen-Display in 6 languages (D, GB, F, Jp, I, ES) and 6 Front controls (Power, Auto, Exit/Volume, Brightness, Contrast, Menu)
User controls	brightness, contrast, colour temperature, sRGB, auto set-up, horizontal / vertical position, clock, phase, sharpness, gamma correction, Eco mode, OSD position, OSD language, reset, volume
Driver	Windows 95 / 98 / 2000 / ME / XP
Ergonomics	TCO'99, MPR III (prEN50279), ISO 13406-2
Safety	TÜV GS, FCC-B, UL / C-UL, CE, VCCI-B
Power supply	AC 100 - 240 V, 50 / 60 Hz
power supply unit	internal
Power usage	max. 30 W in normal use, max. 2 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington®-lock
VESA mounting	75 mm
Tilt angle	25° up
Weight	3,0 with stand kg
Dimensions w x h x d	345 x 341 x 173,5; 345 x 286,5 x 52 without stand mm

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.